

1. **GENERAL**

The marking of the Cable Gland shall include the following:

Ex db I Mb

Ex eb I Mb

Ex db IIC Gb

Ex eb IIC Gb

Ex nR IIC Gc

Ex ta IIIC Da

Ta -60°C to +130°C (standard seal) / -20°C to +200°C (high temperature seal)

The SS2K range of cable glands are intended to terminate circular braided or unarmoured cables into enclosures without compromising the explosion protection provided by the enclosures in accordance with relevant codes of practice. They consist of a male-threaded front entry component, a main body component and an outer seal actuation nut. The front entry component, fitted with an elastomeric sealing ring and a Nylon 6 skid washer, is intended to screw into an entry point of its associated enclosure. The main body component, fitted with a locking ring, threads into the front entry component thereby effecting flameproof and environmental sealing onto the cable inner sheath. The outer seal actuation nut, fitted with an elastomeric sealing ring and a Nylon 6 skid washer, threads into the main body component thereby effecting environmental sealing onto the cable outer sheath. Two versions of the outer seal nut are available to allow alternative sizes of outer sheath to be gripped.

SS2K/PB Range

The SS2K/PB range of cable glands is the same as the SS2K range but the front entry component is fitted with an electrical continuity device for use with lead sheathed cable.

SS2K/TA Range

The SS2K/TA range of cable glands is identical to the SS2K/PB range but is used to terminate circular cables with a tape armour sheath. It is for use in Ex e applications only.

SS2K-FF Range

The SS2K-FF range of cable glands is the same as the SS2K range, but it is fitted with seals suited for use with flat form cables. For use only in Group II applications.

Design options

The front entry component may be manufactured with a profiled groove to captivate an O-ring seal which locates on the mating face with the associated enclosure. This option having the gland type designation prefixed with the letter R, e.g. 25RSS2K

Materials of manufacture:

SS2K/PB, SS2K/TA, and SS2K-FF Ranges of Cable Glands are manufactured in brass, stainless steel, mild steel & aluminium. All brass manufactured component parts can be optionally nickel plated. All mild steel manufactured components can be optionally zinc plated

Examples of alternative entry component thread forms:

- ET(Conduit)
- PG
- BSPP
- BSPT
- ISO
- NPT
- NPSM

Metric entry threads of all model ranges to be manufactured with a pitch between 0.7 mm and 2.0 mm, with 1.5 mm as standard.

The option to manufacture glands with entry threads that are one size up from the nominal quoted gland size.


Alternative material of manufacture of the skid washer to be the same as the gland material.

The front entry component may additionally be fitted with a metallic continuity diaphragm and skid washer for use with lead sheathed cable.

The main body component may additionally be fitted with an electrical continuity device for use with variable speed drive (VSD)/variable frequency drive (VFD) cables.

The option to fit a flat blanking disc between the outer seal and the main body to maintain a minimum IP66 ingress protection. The disc to be marked 'Ex e only' is to indicate that the gland is not suitable for use in Ex d applications when it is fitted.

An optional outer seal nut with an anchor to which hose can be connected by a jubilee clip or similar



The gland and seal sizes are determined by the entry thread and cable range take sizes:

Gland Size	Entry threaded	Entry thread 'B' version	Cable inner seal sheath range Ø (mm)		Cable outer seals heath range Ø(mm)		Alternative outer seal sheath range	
			Min.	Max.	Min.	Max	Min	Max
16	M16 x 1.5	-	3.2	8.7	3.1	8.7	6.1	13.2
20s/16	M20 x 1.5	M25 x 1.5	3.2	8.7	3.1	8.7	6.1	13.2
20s16/20s	M20 X 1.5	M25 x 1.5	3.2	8.7	6.1	11.7	9.5	15.9
20s	M20 X 1.5	M25 x 1.5	6.1	11.7	6.1	11.7	9.5	15.9
20s/20	M20 X 1.5	M25 x 1.5	6.1	11.7	6.5	14.0	12.5	20.9
20	M20 X 1.5	M25 x 1.5	6.5	14.0	6.5	14.0	12.5	20.9
20/25	M20 X 1.5	M25 x 1.5	6.5	14.0	11.1	20.0	18.2	26.2
25	M25 X 1.5	M32 x 1.5	11.1	20.0	11.1	20.0	18.2	26.2
25/32	M25 X 1.5	M32 x 1.5	11.1	20.0	17.0	26.3	23.7	33.9
32	M32 x 1.5	M40 x 1.5	17.0	26.3	17.0	26.3	23.7	33.9
32/40	M32 x 1.5	M40 x 1.5	17.0	26.3	22.0	32.2	27.9	40.4
40	M40 x 1.5	M50 x 1.5	23.5	32.2	22.0	32.2	27.9	40.4
40/50s	M40 x 1.5	M50 x 1.5	23.5	32.2	29.5	38.2	35.2	46.7
50s	M50 x 1.5	M63 x 1.5	31.0	38.2	29.5	38.2	35.2	46.7
50s/50	M50 x 1.5	M63 x 1.5	31.0	38.2	35.6	44.1	40.4	53.1
50	M50 x 1.5	M63 x 1.5	35.6	44.1	35.6	44.1	40.4	53.1
50/63s	M50 x 1.5	M63 x 1.5	35.6	44.1	40.1	50.1	45.6	59.4
63s	M63 x 1.5	M75 x 1.5	41.5	50.0	40.1	50.1	45.6	59.4
63s/63	M63 x 1.5	M75 x 1.5	41.5	50.0	47.2	56.0	54.6	65.9
63	M63 x 1.5	M75 x 1.5	47.2	56.0	47.2	56.0	54.6	65.9
63/75s	M63 x 1.5	M75 x 1.5	47.2	56.0	52.8	62.0	59.0	72.1
75s	M75 x 1.5	M90 x2.0	54.0	62.0	52.8	62.0	59.0	72.1

75s/75	M75 x 1.5	M90 x2.0	54.0	62.0	59.1	68.0	66.7	78.5
75	M75 x 1.5	M90 x2.0	61.1	68.0	59.1	68.0	66.7	78.5
75/90	M75 x 1.5	M90 x2.0	61.1	68.0	66.6	79.4	76.2	90.4
90	M90 x 2.0	M100 x 2.0	66.6	80.0	66.6	79.4	76.2	90.4
90/100	M90 x 2.0	M100 x 2.0	66.6	80.0	76.0	91.0	86.1	101.5
100	M100 x 2.0	M115 x 2.0	76.0	91.0	76.0	91.0	86.1	101.5
100/115	M100 x 2.0	M115 x 2.0	76.0	91.0	86.0	98.0	101.5	110.3
115	M115 x 2.0	M130 x 2.0	86.0	98.0	86.0	98.0	101.5	110.3
115/130	M115 x 2.0	M130 x 2.0	86.0	98.0	97.0	115.0	110.2	123.3
130	M130 x 2.0	Not available	97.0	115.0	97.0	115.0	110.2	123.3

Cable sizes for the SS2K-FF range only

Gland Size	Entry threaded	Entry thread 'B' version	Cable inner seal sheath range Ø (mm)		Cable outer seals heath range Ø(mm)	
			Min.	Max.	Min.	Max
20s	M20 x 1.5	M25 x 1.5	4.0 x 6.2	6.8 x 11.7	4.0 x 6.2	6.8 x 11.7
20	M20 x 1.5	M25 x 1.5	5.7 x 8.0	8.7 x 13.5	5.7 x 8.0	8.7 x 13.5

Based on the following documentation: IECEx CML 18.0178X. Issue 1.

2. INSTALLATION INSTRUCTIONS

It is the manufacturer's responsibility to supply installation instructions with each unit offered for sale as required by IEC/SANS 60079-0 Clause 30.

3. SPECIAL CONDITIONS FOR SAFE USE *(denoted by "X" after certificate number)*

The following conditions relate to safe installation and/or use of the equipment.

- i. When the cable glands are supplied with an entry thread that is one size up from the nominal gland size, designated with the letter 'B' after the gland size, e.g. 32B****, they shall not be used with any adaptor device.

4. SCHEDULE OF LIMITATIONS *(denoted by "U" after certificate number)*

None.

5. CONDITIONS OF CERTIFICATION

All production units must be covered by a QAN (Quality Assurance Notification), Product Mark Scheme or batch evaluation.

6. MARKING

The following (or similar) information have to be clearly and permanently marked on all units:

Supplier : CMP Products Limited
 Manufacturer : CMP Products Limited
 Equipment : Cable Gland
 Model/Type : Types SS2K**
 Serial No. : ---
 Ex Rating : Ex db I Mb

Ex eb I Mb

Ex db IIC Gb

Ex eb IIC Gb

Ex nR IIC Gc

Ex ta IIIC Da

Ta -60°C to +130°C (standard seal) / -20°C to +200°C (high temperature seal)

IA Certificate No : MS-XPL/21.0007 X

